



MATERIAL SAFETY DATA SHEET

Olin MSDS No.: 00052.0001
Revision No.: 18

Revision Date: 1/1/13
Supersedes: 7/26/12

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: CENTERFIRE BLANK ROUNDS
Chemical Name: Mixture – Metal Alloy
Synonyms: Centerfire Blanks, Super X Centerfire Blank Cartridge, 32 Smith & Wesson, 38 Special, Cartridge 5.56 M200 Blank, SRTA (Short Range Training Ammunition)
Chemical Family: Metal mixture
Formula: Not applicable - mixture
Product Use/ Description: Ammunition – Centerfire blank load

COMPANY ADDRESS MSDS Control Group
Olin Corporation – Winchester
Division, Inc.
600 Powder Mill Road
East Alton, IL 62024
www.winchester.com

**TECHNICAL
INFORMATION:**
618-258-3507

EMERGENCY TELEPHONE NUMBER:
US/Canada: 1-800-424-9300
Outside US/Canada: 703-527-3887
Customer #: ccn24728

2. COMPOSITION / INFORMATION ON INGREDIENTS

CAS Number	Components	% By Weight	EINECS/ ELINCS #	EU Classification	
				Symbol	R-Phrase
7440-50-8	Copper	40 - 75	231-159-6	None	None
7440-66-6	Zinc	20 – 35	231-175-3	F (as dust or powder)	R 15-17
9004-70-0	Nitrocellulose	2 - 17	Not listed	E*	R 2
55-63-0	Nitroglycerin	1 - 3	200-240-8	E, T+, N	R 3-26/27/28-33-51-53
84-74-2	Dibutyl phthalate	0.2 - 3	201-55-74	None	None
15245-44-0	Normal Lead styphnate	0.1 - 1	239-290-0	E, T, N	R61-3-20/22-33-50/53-62

*This material is not listed in Annex 1 of Directive 88/379/EEC. Olin has classified the material according to the conventional method based upon information from similar materials.

OSHA REGULATORY STATUS: Explosive

3. HAZARDS IDENTIFICATION

CAUTION!

EXPLOSIVE. KEEP AWAY FROM HEAT. DO NOT SUBJECT TO MECHANICAL SHOCK. PARTICLES FROM FIRING MAY BE HARMFUL IF INHALED. DO NOT TAKE INTERNALLY.

HAZARD RATINGS (for dust or fume)
Hazardous Materials Identification System (HMIS)

Degree of hazard (0 = low, 4 = extreme)
Health: 0 Flammability: 1

Physical Hazard:
Explosive: 2

National Fire Protection Association (NFPA)

Mixture. Not rated.

HUMAN THRESHOLD RESPONSE DATA

Odor Threshold:

Unknown

Irritation Threshold:

Unknown

Immediately Dangerous to Life or Health (IDLH) Value(s):

The IDLH for this product is not known. The IDLH for copper and lead is 100 mg/m³. The IDLH for nitroglycerin is 75 mg/m³. The IDLH for dibutyl phthalate is 4000 mg/m³

POTENTIAL HEALTH EFFECTS

This product is composed of a finished metal alloy cartridge which contains the various components completely sealed within. Therefore, under normal handling of this product, no exposure to any harmful materials will occur.

When the ammunition is fired, a small amount of particles may be generated which may be slightly irritating to the eyes and the respiratory tract. The particles may contain trace amounts of these harmful substances:

Copper: Inhalation of high concentrations of metallic copper dusts or fumes may cause nasal irritation and/or nausea, vomiting and stomach pain.

Nitroglycerin: Will produce dilation of blood vessels and drop in blood pressure which may affect the heart. It has also been shown to cause methemoglobinemia (cyanosis).

Lead: Ingestion of large amounts of lead can cause abdominal pain, constipation, cramps, nausea and/or vomiting. Chronic exposure to lead can cause kidney damage, anemia, reproductive effects, developmental effects and permanent nervous system damage in humans including changes in cognitive function.

It is unlikely that the amount of particles that someone would be exposed to from firing this product would be sufficient to cause any of these effects.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: There are no medical conditions known to be aggravated by exposure to this product in its solid form. Exposure to lead can aggravate anemia, cardiovascular and respiratory disease.

POTENTIAL ENVIRONMENTAL EFFECTS: Product has not been tested for environmental properties. Lead has been shown to be toxic to aquatic species.

4. FIRST AID MEASURES

EYE CONTACT: Immediately flush out fume or particles with large amounts of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. If eye irritation develops, call a physician at once.

SKIN CONTACT: Wash skin with plenty of soap and water.

INHALATION: If symptoms of lung irritation occur (coughing, wheezing or breathing difficulty), remove from exposure area to fresh air immediately. If breathing has stopped, perform artificial respiration. Keep affected person warm and at rest. Get medical attention.

INGESTION: If ingested, immediately call a physician.

5. FIRE FIGHTING MEASURES

PROPERTY	VALUE	PROPERTY	VALUE
Explosive	Yes	Flammable	Not applicable
Combustible	Not applicable	Pyrophoric	No
Flash Point (°C):	Not applicable	Burning Rate of Material:	Not applicable
Lower Explosive Limit:	Not applicable	Autoignition Temp.:	No data
Upper Explosive Limit:	Not applicable	Flammability Classification: (defined by 29 CFR 1910.1200)	Explosive

UNUSUAL FIRE AND EXPLOSION HAZARDS: None.

EXTINGUISHING MEDIA: Flood area with water. If no water is available, carbon dioxide, dry chemical or earth may be used.

SPECIAL FIREFIGHTING PROCEDURES: In case of fire or if the fire reaches cargo, use normal fire fighting equipment. Turnout gear supplies sufficient fire fighter protection from the explosive characteristics of this product.

6. ACCIDENTAL RELEASE MEASURES

FOR ALL TRANSPORTATION ACCIDENTS, CALL CHEMTREC AT 800-424-9300.

Spills of this material should be handled carefully. Do not subject materials to mechanical shock. A spill of this material will normally not require emergency response team capabilities. If, however, a large spill occurs, call 1-888-289-1911 for technical assistance.

7. HANDLING AND STORAGE

HANDLING: No special requirements
STORAGE: No special requirements
Shelf Life Limitations: Not known
Incompatible Materials for Packaging: None known
Incompatible Materials for Storage or Transport: Acids, Class A & B explosives, strong oxidizers, and caustics
CONDITIONS TO AVOID: None

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CAS #	CHEMICAL NAME	ACGIH TLV	OSHA PEL	INTERNATIONAL OELS
7440-50-8	Copper	0.2 mg/m ³ (fume), 1 mg/m ³ (dusts and mists)	0.1 mg/m ³ (fume) 1 mg/m ³ (dusts and mists)	Austria, Belgium, Canada: 0.2 mg/m ³ (fumes), 1 mg/m ³ (dusts) Denmark: 1.0 mg/m ³ (dust and powder) Germany (MAK): 0.1 mg/m ³ (fume), 1 mg/m ³ (dusts and mists)
7440-66-6	Zinc	None established	None established	None established
9004-70-0	Nitrocellulose	None established	None established	None established
55-63-0	Nitroglycerin	0.05 ppm (0.46 mg/m ³) Skin	Ceiling – 0.2 ppm (2 mg/m ³) Skin	Denmark: 0.02 ppm (0.2 mg/m ³) Norway, Sweden: 0.03 ppm (0.3 mg/m ³) Austria, Belgium, Germany, The Netherlands, Poland, Switzerland: 0.05 ppm (0.47 mg/m ³), skin Finland, France: 0.1 ppm (0.9 mg/m ³), skin U.K.: 0.2 ppm (2 mg/m ³), skin
84-74-2	Dibutyl phthalate	5 mg/m ³	5 mg/m ³	Belgium, Denmark, France, Netherlands, Switzerland, U.K.: 5 mg/m ³ Sweden: 3 mg/m ³
15245-44-0	Lead styphnate	None established	None established	None established

ENGINEERING CONTROLS: Local exhaust ventilation is recommended if significant dusting occurs or fumes are generated. Otherwise, use general exhaust ventilation. Use hearing protection.
EYE / FACE PROTECTION: Use safety glasses.
SKIN PROTECTION: Not normally needed
RESPIRATORY PROTECTION: Respiratory protection not normally needed.
GENERAL HYGIENE: Do not eat, drink, or smoke while using this product. Wash hands thoroughly after use.

9. PHYSICAL AND CHEMICAL PROPERTIES

PROPERTY	VALUE	PROPERTY	VALUE
<i>Appearance:</i>	Cylindrical brass cartridge	<i>Vapor Density (air = 1):</i>	Not applicable
<i>Odor:</i>	None	<i>Boiling Point (°F):</i>	Not applicable
<i>Molecular Weight:</i>	Not applicable - Mixture	<i>Melting point:</i>	Not applicable
<i>Physical State:</i>	Solid	<i>Specific gravity (g/cc):</i>	Not applicable
<i>pH:</i>	Not applicable	<i>Bulk Density:</i>	Not applicable
<i>Vapor Pressure (mm Hg):</i>	Not applicable	<i>Viscosity (cps):</i>	Not applicable
<i>Vapor Density:</i>	Not applicable	<i>Decomposition Temperature:</i>	Not applicable
<i>Solubility in Water (20 °C):</i>	Insoluble	<i>Evaporation Rate:</i>	Not applicable
<i>Volatiles, Percent by volume:</i>	Not applicable	<i>Octanol/water partition coefficient:</i>	Not applicable

10. STABILITY AND REACTIVITY

STABILITY: Stable under normal temperatures and pressure.
MATERIALS TO AVOID: Acids, Class A & B explosives, strong oxidizers, and caustics
HAZARDOUS DECOMPOSITION PRODUCTS: Nitrogen oxides, carbon monoxide, lead oxides, carbon dioxide, lead dust/fume
HAZARDOUS POLYMERIZATION: Will not occur.
OTHER: Cartridge may detonate if case is punctured or severely damaged.

